

Monitor 4POS

Due to its robust aluminium die-cast housing, the 4POS monitor is fit for industrial applications as well as in POS areas, and is superior to other touch monitors in plastic housings. In spite of its slim base, the monitor stands extremely stable. Another plus: it can be mounted simply to the wall. With its optional accessories like customer display, magnet card reader, i-button and keyboard, the 4POS monitor is suitable for a wide variety of applications.



Technische Daten

Display

ACD 121TA-B: TFT 12,1", ELO resistive Touch

ACD 121A-B: TFT 12,1", without Touch

ACD 152TA-B: TFT 15", ELO resistive Touch

ACD 152A-B: TFT 15", without Touch

Solution

TFT 12,1": 800 x 600 (SVGA) colour LCD

TFT 15": 1024 x 768 (SVGA) colour LCD

Brightness

TFT 12,1": 180 cd/m², **TFT 15":** 250 cd/m²

Display Tilt

90° upright, 180° flat

Ausstattung

Touch version: 5-wire resistive touch screen digital LVDS

Interface

Powersupply

Slot-Steelplate directly from PC or power supply (ZF-PSU25W Power supply 25W 12 V DC)

Dimensions in mm

Height: **TFT 12,1":** 290, **TFT 15":** 330, Display standing upright, base (W x D): **TFT 12,1":** 198 x 172, **TFT 15":** 200 x 200, Width: **TFT 12,1":** 315, **TFT 15":** 360, with magnet card reader:

TFT 12,1": 360, **TFT 15":** 405

Colour

black, grey, silver, aluminium die-cast housing

Options

customer display 2 x 20 VFD, magnet card reader, 32 keyboard with and without waiter's lock

Optionen

