

# 4POS



## System

|                       |                                                             |
|-----------------------|-------------------------------------------------------------|
| <b>CPU</b>            | Intel® Atom™ processor Z510/Z530 up to 1.6 GHz              |
| <b>Cache Memory</b>   | 512K 2nd level cache memory                                 |
| <b>System Chipset</b> | Intel® System control hub US15W                             |
| <b>System Memory</b>  | Default 1GB, maximum 2GB<br>(SO-DIMM, 1 x 200-pin DDR2 533) |

## Storage

|                   |                               |
|-------------------|-------------------------------|
| <b>HDD Driver</b> | 1 x 2.5" SATA HDD bay         |
| <b>SSD</b>        | 1 x Type II CompactFlash slot |

## Display

|                    |                                                                   |
|--------------------|-------------------------------------------------------------------|
| <b>Chipset</b>     | Intel® System Control Hub US15W<br>Graphics Media Accelerator 500 |
| <b>Memory Size</b> | Support Intel® DVM T, Share system memory up to 254 MB            |

## I/O

|                       |                                                      |
|-----------------------|------------------------------------------------------|
| <b>Serial Port</b>    | 5 x External (all Pin 9 with +5V/12V): COM 1/2/4/5/6 |
| <b>USB Port</b>       | 7 x External USB: 1 x front, 6 x rear                |
| <b>VGA Port</b>       | 1 x 15 pin D-Sub VGA output                          |
| <b>PS2 KB / Mouse</b> | 1 x PS2 connector                                    |
| <b>Parallel Port</b>  | 1 x bi-directional parallel ( D-Sub25 )              |
| <b>Audio</b>          | 1 x Line-out, 1 x Mic-in                             |
| <b>Ethernet</b>       | 1 x RJ-45 Gigabit Ethernet (10/100/1000)             |
| <b>Cash Drawer</b>    | 1 x RJ11 (12V, single/dual)                          |

## Mechanical and Environment

|                              |                           |
|------------------------------|---------------------------|
| <b>Case Material</b>         | Aluminum enclosure        |
| <b>Color Option</b>          | Red                       |
| <b>Power Supply</b>          | 60W 12Vdc power adapter   |
| <b>Operation Temperature</b> | 0°C ~ 35°C operating      |
| <b>Dimensions</b>            | 163.5(D) x 235(W) x 64(H) |
| <b>Weight</b>                | 2.5kg                     |
| <b>EMI / Safety</b>          | CE, FCC, CB, RoHS         |

## Software

|                   |                                                                   |
|-------------------|-------------------------------------------------------------------|
| <b>OS Support</b> | XP Pro Embedded , Windows Embedded POSReady<br>2009, WEPOS, Linux |
|-------------------|-------------------------------------------------------------------|

Eutronix SA/NV  
Avenue Zénobe Gramme 29  
B-1300 Wavre  
BELGIUM  
Tel: +32 (0)10.39.49.00  
Fax: +32 (0)10.39.49.01  
Web: [www.eutronix.eu](http://www.eutronix.eu)  
Email: [info@eutronix.eu](mailto:info@eutronix.eu)

